Fly

Massimiliano Raggi



SO

AP

PICTURE

Un segno deciso.
Una barra luminosa, sottile come una lama , potente come un taglio. Fly è una lampada duttile utilizzabile in più ambienti della casa o in ambito contract/hospitality e con l'associazione del diffusore tessile superiore o frontale nella versione a muro diventa un elemento di arredo, quasi una scultura luminosa soprattutto quando si presenta in ripetizione o in associazione di misure differenti. La sua trasversalità e la sua modernità sono manifeste, il suo utilizzo molto ampio.

A decisive statement.
A light-bar that is as thin as a blade, as sharp as a cut. Fly is a flexible lamp that can be used in several rooms of the house, or in the contract and hospitality sector. When used with the upper or front textile diffuser in the wall version, it becomes a piece of furniture – almost a luminous sculpture, especially when it is repeated, or combined in different ways. The lamp's versatility and its modernity are evident, with a wide range of applications.

SPECIFICHE PRODOTTO / PRODUCT SPECIFICS p.2

FLY SO L.120 p.3
FLY SO L.170 p.4

FLY AP p.5
FLY AP VELA p.6

FLY PICTURE p.7

contardi

STRUTTURA / *FRAME*

Nickel dorato satinato
Satin gold nickel

STRUTTURA / *FRAME*

Tessuto effetto marmo bianco Calacatta
White Calacatta marble printed fabric

Cotone bianco
White cotton

FONTE LUMINOSA / *LIGHT SOURCE*

220-240V

Strip LED

SO L.120 (Doppia emissione / *Double emission*)
Superiore / *Upper*
1 x 17W
Strip LED
Emissione / Light emission: 2.000 Lm

Inferiore / *Lower*
1 x 23W
Strip LED
Emissione / Light emission: 2.800 Lm

2.700 K; CRI: >90
IP20

SO L.170 (Doppia emissione / *Double emission*)
Superiore / *Upper*
1 x 24W
Strip LED
Emissione / Light emission: 3.000 Lm

Inferiore / *Lower*
1 x 33W
Strip LED
Emissione / Light emission: 4.000 Lm

2.700 K; CRI: >90
IP20

AP (Doppia emissione / *Double emission*)
Fronte-Retro / *Front-Back*
1 x 21W
Strip LED
Emissione / Light emission: 2.600 Lm
2.700 K; CRI: >90
IP20

PICTURE
1 x 12W
Strip LED
Emissione / Light emission: 1.500 Lm
2.700 K; CRI: >90
IP20

Dimmerabile DALI/Push.
Altri sistemi di dimmerazione disponibii su richiesta

DALI/Push dimmable.
Other dimming systems available on request

110V

Strip LED

SO L.120 (Double emission)
Upper
1 x 17W
Strip LED
Light emission: 2.000 Lm

Lower
1 x 23W
Strip LED
Light emission: 2.800 Lm

2.700 K; CRI: >90
IP20

SO L.170 (Double emission)
Upper
1 x 24W
Strip LED
Light emission: 3.000 Lm

Lower
1 x 33W
Strip LED
Light emission: 4.000 Lm

2.700 K; CRI: >90
IP20

AP (Double emission)
Front-Back
1 x 21W
Strip LED
Light emission: 2.600 Lm
2.700 K; CRI: >90
IP20

PICTURE
1 x 12W
Strip LED
Light emission: 1.500 Lm
2.700 K; CRI: >90
IP20

1...10V dimmable.
Other dimming systems available on request

CE

contardi


1168mm
[45,98in]
156mm
[6,14in]
220mm
[8,66in]
45mm
[1,77in]
80mm
[3,15in]
2000mm
[78,74in] ADJUSTABLE
188mm
[7,39in]
50mm
[1,96in]
105mm
[4,11in]
1200mm
[47,24in]
14mm
[0,55in]




1668mm
[65,67in]
156mm
[6,14in]
220mm
[8,66in]
45mm
[1,77in]
80mm
[3,15in]
2000mm
[78,74in] ADJUSTABLE
160mm
[6,28in]
50mm
[1,96in]
105mm
[4,11in]
1700mm
[66,93in]
14mm
[0,55in]




55mm
[2,17in]
40mm
[1,57in]
14mm
[0,55in]
101mm
[3,99in]
50mm
[1,96in]
32mm
[1,24in]
1499mm
[59,02in]
440mm
[17,32in]
420mm
[16,54in]
60mm
[2,36in]
14mm
[0,55in]


55mm
[2,17in]
40mm
[1,57in]
66mm
[2,59in]
14mm
[0,55in]
300°
123mm
[4,82in]
50mm
[1,96in]
32mm
[1,24in]
1513mm
[59,57in]
440mm
[17,32in]
420mm
[16,54in]
60mm
[2,36in]
102mm
[4,02in]


50mm
[1,96in]
53mm
[2,09in]
40mm
[1,57in]
90°
14mm
[0,55in]
604mm
[23,78in]
310mm
[12,20in]
50mm
[1,97in]
300mm
[11,81in]
30mm
[1,18in]
2mm
[0,06in]
14mm
[0,55in]
99mm
[3,88in]

Copyright and/or design rights subsist in this drawing. No part of this drawing may be reproduced in any material form (including photocopying or storing in any medium electronic means,
whether or not intentionally and whether or not as part or a larger publication) without the express permission of the copyright owner, Contardi Lighting S.r.l.. Further and without prejudice to the
above, this drawing and all information relating thereto is confidential, and shall not be communicated to a third party without the consent of Contardi lighting srl. Contardi lighting srl asserts
all rights to be identified as the author of the work and otherwise.

WARNING: The doing of any unauthorised act in relation to a copyright work may result in both a civil claim for damages and criminal prosecution.

CONTARDI LIGHTING Srl
ITALY HEADQUARTERS
www.contardi-italia.com / sales@contardi-italia.it

CONTARDI USA Inc
USA BRANCH
www.contardi-usa.com / sales@contardi-usa.com

contardi